



Coated Webbing

Description

Product Type	Coated webbing
Material	polyester + soft plastic (synthetic material)
Techniques	coated
Width	0.4~2 inch
Thickness	1.0~3.5 mm
Length	Customized
Color	Customized
Endurance	920 lbs at maximum
Thermal Tolerance	80°C at maximum
Usage	Bags, Garment, dog collar and leash, etc
Place of Origin	Guangdong, China (Mainland)

● Advantages:

Soft, will not rein hands, high environmental production, convenience for processing(Printing pattern, sewing convenience), waterproof and easy to clean, high-grade appearance, will not fade easily, the p pattern does not fall off, not unglued and hierarchical.

● Applications:

Applied to pet collars leashes, luggage, sports equipment, outdoor supplies etc.



● **Stock Dimension Table:**

Webbing Size(mm)	Thickness(mm)	Packing
50	2.8~3.5mm	50 meters per roll
38	1~2mm	50 meters per roll
25	1~2mm	50 meters per roll
20	1~2mm	50 meters per roll
16	1~2mm	50 meters per roll
10	1~2mm	50 meters per roll

Detailed Images

What is Coated Webbing?





Printed Pattern Coated Webbing

Since 2009



www.gh-material.com

Since 2009



www.gh-material.com

Finished Product

Since 2009



www.gh-material.com

Since 2009



www.gh-material.com



Guanghai Electric Insulation Materials Co., Ltd

Guanghai Electronic Insulation Materials Co.,Ltd professional in kind of insulation tubes and coated webbing , any interested ,please contact us: info@gh-material.com

Address :(Plant) 3/F, No. 154, Huasheng East St.
Chenjiang Street, Zhongkai High-Tech Zone,
Huizhou, Guangdong, China (Mainland)
Tel/Fax:86-752-3175209
Website: <http://www.gh-material.com>

